

Woody's® Track Drill Instructions

Verify and follow the snowmobile and track manufacturer's studding recommendations. The addition of studs may effect your track warranty and track longevity.

Track Drill

Tools Needed:

Power Drill Track Drill Side Cutters



Important - Confirm before drilling that you have marked ONLY the holes adjacent to the letter that applies to your pattern per the directions with the Woody's template. Check the entire track.

Before drilling, confirm there is clearance for the Track Drill to protrude on the other side of the track. It is essential not to let the drill touch the idler wheels or any other component of the snowmobile.

During use, the Track Drill can get hot. Do not touch the Track Drill during use. The track plugs created can also be hot. Use gloves, eye protection and long sleeved clothing while drilling the holes.

1. Attach a Woody's 1/4" Track Drill for 7mm studs (Part # DRIL-1/4) or a 7mm Track Drill for 5/16" (Part # DRIL-7MM) studs to a power drill.
2. Center the Track Drill attached to the drill over a mark that indicates the stud pattern. Then using slight pressure, drill through the track belt. Repeat until all marks are drilled.



3. Inspect the track for any plugs that are still attached to the track. Use side cutters to remove any excess rubber.
4. Begin installing a stud in each hole drilled. Refer to the installation instructions included in the stud package. (Part # INST-WDYS-MASTER-2) These instructions are also available on www.woodystraction.com.

CONTACTING US & TECHNICAL ASSISTANCE

We have experienced technicians to assist you. For a prompt response E-mail us at woody@wiem.com. Otherwise you can contact us from 8:00 a.m. to 4:30 p.m. (EST), Monday through Friday. Phone: 989-689-4911 Fax: 989-689-4910 If you need assistance in locating a supplier near you log onto www.woodystraction.com and go to our Dealer Locator.

⚠ WARNING

- NEVER STAND BEHIND or near a rotating track with/without a jack stand or back stand or kick stand.
- Do not lift rear of snowmobile track while operating.
- Track failure or debris can project with great force resulting in personal injury, dismemberment or death.



⚠ AVERTISSEMENT

- NE JAMAIS SE TENIR DERRIÈRE ou près d'une chenille qui tourne, avec ou sans béquille, chandelle ou support central.
- Ne pas soulever l'arrière de la chenille de la motoneige lorsque celle-ci tourne.
- Une chenille brisée ou des débris pourraient être projetés avec force et pourraient ainsi sectionner une jambe ou causer d'autres blessures sérieuses, voire la mort.

Part# INST-WDYS-TRAKDRIL-2